space with said free ends in contact with said head, and at least a portion of said head-receiving space having a circumference which is greater than said circumference of said opening whereby, in use, when said device is lowered on to said head so that said head enters said head-receiving space through said opening, said free ends of said fingers apply pressure to and thus massage said head.

15
~~22~~. The device according to claim 14, wherein each said free end of each said finger is smoothly terminated.

16
~~23~~. The device according to claim 15, wherein each said free end is terminated in a bulb or ball-like structure.

17
~~24~~. The device according to claim 2, wherein said fingers comprise wire.

6
~~25~~. The device according to claim 4, wherein said fingers are electrically conductive.

5
~~26~~. The device according to claim 2, wherein said fingers comprise copper wire.

17
~~27~~. The device according to claim 14, wherein said device comprises from four to twenty-four said fingers.

18
~~28~~. The device according to claim 14, wherein said connected opposite ends of said fingers terminate in or form a handle for gripping and manipulating said massaging device.

11

B

19
~~29~~. A head massaging device comprising a plurality of resilient fingers, said fingers each having a free end and an opposite end, said opposite ends being connected together and terminating in or forming a handle for gripping and manipulating said

massaging device, each of said fingers having a transversely extending portion immediately adjacent the handle, each said transversely extending portion being followed by a contiguous portion extending downwardly and inwardly from said transversely extending portion, said contiguous portion terminating in said free end, said ~~intermediate length and continuous length~~ of said fingers together defining a head-receiving space for receiving a ~~space,~~ head said space extending between said free ends and said opposite ends and having an opening at one end formed by a juxtaposition of said free ends of said fingers, said opening having a circumference smaller than a circumference of said head, and at least a portion of said head-receiving space having a circumference which exceeds said circumference of said opening whereby, in use, when said device is lowered on to said head so that said head enters said head-receiving space through said opening, said free ends of said fingers apply pressure to and thus massage said head.

20 19
~~30~~. The device according to claim ~~29~~, wherein said fingers are pliable so that the size and shape of said opening can be varied.

21 19
~~31~~. The device according to claim ~~29~~, wherein each said free end of each said finger is smoothly terminated.

22 19
~~32~~. The device according to claim ~~31~~, wherein each said free end is terminated in a bulb or ball-like structure.

12